

Insight vs IES on a Net-Zero Project: Building Performance Modeling Best Practices

Xiaofei Shen

About the speaker

Xiaofei Shen

AIA, LEED AP, WELL AP

Architect/ Sustainability Engineer in AECOM New York.

His effort has been devoted to crossing the line
between artistic design and scientific method through
parametric performance simulation, generative design
optimization, and interactive data visualization.

LEARNING OBJECTIVES

WHY INSIGHT

Learn why the team determined to use Insight as one of the building performance analysis tools for future projects

INSIGHT USES


Discover how Insight and other tools were used in designing a net-zero project from concept to documentation

BEST PRACTICE

Explore the best approaches to modeling in Revit to achieve reliable simulation results from Insight

PICK N CHOOSE

Learn the pros /cons when comparing Insight, IES VE, and Honeybee, and select the tool that is right for your project



STEM CENTER

Designed for Net Zero Energy Capable
and LEED Platinum Capable.

WHY INSIGHT?

From Code Compliance to Net Zero Capable

Learn why the team
determined to use Insight
and other environmental
performance analysis tools
for future projects

Challenge 1 Net Zero Building Design

Challenge 2 Gap between BEM and BIM

WHY INSIGHT?

CHALLENGE 1

in Net Zero Building Design



When do we need a Building Energy Model (BEM)?

Type A

Energy Code Compliance

Type B

High Performance Design Optimization

Type C

Net Zero Energy Achievability Verification

Building Energy Model (BEM)

Type A Code Compliance Model



- DESIGN IS CONFIRMED
- PROCESS IS STRAIGHT FORWARD. SINGLE MODEL.
- ASSUMPTIONS ARE ACCEPTABLE

	Code Compliance		
Massing Design	confirmed		
Envelope Design	confirmed		
Layout/ Zoning	confirmed		
Building Profile	assumption		
Equipment Load/ Control	assumption		
Lighting Load/ Control	confirmed		
HVAC Type	confirmed		
HVAC Settings	confirmed		

Building Energy Model (BEM)

Type B High Performance Design



- DESIGN SHALL BE OPTIMIZED
- PROCESS IS BACK AND FORTH. MULTIPLE MODELS.
- ASSUMPTIONS ARE ACCEPTABLE

	Code Compliance	High Performance	
Massing Design	confirmed	optimized	
Envelope Design	confirmed	optimized	
Layout/ Zoning	confirmed	optimized	
Building Profile	assumption	assumption	
Equipment Load/ Control	assumption	assumption	
Lighting Load/ Control	confirmed	optimized	
HVAC Type	confirmed	optimized	
HVAC Settings	confirmed	optimized	

Building Energy Model (BEM)

Type C Net Zero Design



- DESIGN SHALL BE OPTIMIZED
- PROCESS IS BACK AND FORTH. MULTIPLE MODELS.
- ASSUMPTIONS SHALL BE PRECISE
- A typical Net Zero project usually requires additional time to design/ deliver.

	Code Compliance	High Performance	Net Zero
Massing Design	confirmed	optimized	optimized
Envelope Design	confirmed	optimized	optimized
Layout/ Zoning	confirmed	optimized	optimized
Building Profile	assumption	assumption	as built
Equipment Load/ Control	assumption	assumption	as built
Lighting Load/ Control	confirmed	optimized	optimized
HVAC Type	confirmed	optimized	optimized
HVAC Settings	confirmed	optimized	optimized

WHY INSIGHT?

CHALLENGE 2

in Bridging BEM & BIM



Three Questions

Question 1

A SEPARATE BEM MODEL IS ALWAYS NEEDED?

Question 2

SHALL WE HOLD OFF BEM UNTIL BIM IS FULLY READY?

Question 3

LACK OF UNIFORM BEM STANDARD IN BIM?

Question 1


A SEPARATE BEM MODEL IS ALWAYS NEEDED?

MUCH DUPLICATED EFFORT OCCURS WHEN EXCHANGING BETWEEN BEM AND BIM. **NOT EFFICIENT!**


NO

- Revit offers an extensible medium for data storage which provides opportunities to include BEM parameters, so the separation can be avoided.
 - gbXML. Building data can be exchanged without repeating the work.
 - Insight. No exchanges between the models. Integrated simulation capabilities in BIM are available.
- **TIME AND COST SAVING**


Revit



IES



Insight




Question 2

SHALL WE HOLD OFF BEM UNTIL BIM IS FULLY READY?

MOST BEM OCCURS WHEN NEARING BIM COMPLETION WHEN DATA IS COLLECTED. **TOO LATE!**

NO

- BIM offers a platform where inputs and assumptions can be filled in the model directly, so the BEM can proceed earlier.
 - gbXML. Default energy settings with reasonable multi-disciplinary assumptions can be passed through for BEM at the early stage.
 - Insight. Different Level of Details (LOD) are acceptable which allows the BEM functionality to be integrated at different BIM stages.
- **EARLIER AND BETTER ESTIMATES!**



Question 3

NO UNIFORM BEM STANDARD IN BIM?

NO ESTABLISHED BEM STANDARD IN BIM WHEN DEFINING PROPERTIES. **ACCURACY NOT GUARANTEED!**

NO

- BIM provides the methodology to transfer information more effectively than multiple formats.
 - BIM templates. Pre-defined BIM templates can be utilized between different projects and professionals
 - Insight. A more integrated design tool without transferring the information.
- **REDUCED RISKS**

Revit Space

<Space Schedule>								
A	B	C	D	E	F	G	H	I
Name	Space Type	Area	Area per P	Specified Light	Specified Powe	Outdoor Air p	Outdoor Air pe	Specified Exha
Admin	BBJ Admin	2968 SF	200 SF	0.30 W/ft ²	0.75 W/ft ²	5.0 CFM	0.06 CFM/SF	0.00 CFM
Barber	BBJ Multi-purpos	602 SF	10 SF	0.40 W/ft ²	0.50 W/ft ²	7.5 CFM	0.06 CFM/SF	0.00 CFM
Cell	BBJ Cell	65693 SF	40 SF	0.64 W/ft ²	0.10 W/ft ²	5.0 CFM	0.06 CFM/SF	1.00 CFM
Central Control	BBJ Central Contr	5910 SF	200 SF	0.30 W/ft ²	0.75 W/ft ²	5.0 CFM	0.06 CFM/SF	0.00 CFM
Children's Play	BBJ Community	1423 SF	10 SF	0.62 W/ft ²	1.00 W/ft ²	7.5 CFM	0.12 CFM/SF	0.00 CFM
Clinic	BBJ Medical	15475 SF	50 SF	0.56 W/ft ²	5.00 W/ft ²	15.0 CFM	0.00 CFM/SF	
Community	BBJ Community	36374 SF	10 SF	0.62 W/ft ²	1.00 W/ft ²	7.5 CFM	0.12 CFM/SF	0.00 CFM
Concourse	BBJ Corridor	108192 SF	1000 SF	0.41 W/ft ²	0.10 W/ft ²	0.0 CFM	0.06 CFM/SF	0.00 CFM
Conference	BBJ Admin	1636 SF	200 SF	0.30 W/ft ²	0.75 W/ft ²	5.0 CFM	0.06 CFM/SF	0.00 CFM

eQuest Space


	Space Name	Parent Floor	Activity Desc.	Occupancy Schedule	Area/Person (ft2)	Number of People	Total Ht Gain (Btu/h-person)	People Sens (Btu/h-person)	People Lat (Btu/h-person)
45	EL3 (FL3) Nurse's Office	EL3 Third floor	Healthcare - Exam	OFFICE-OCC-YR	58	1.00	450	250	200
46	EL1 (FL1) Warming Pantry	EL1 First floor	Food Preparation	KITCHEN-OCC-YR	200	11.00	450	275	275
47	EL2 (FL2) Exercise Room	EL2 Second floor	Exercise Room	GYM-OCC-YR	17	31.00	450	710	1,090
48	EL1 (FL1) Domestic Water S	EL1 First floor	Electrical/Mechanic	NULL-OCC-YR	300	0.00	450	250	200
49	EL1 (FL1) Refuse/Recycle	EL1 First floor	Electrical/Mechanic	NULL-OCC-YR	300	0.00	450	250	200
50	EL2 (FL2) Telecom	EL2 Second floor	Electrical/Mechanic	NULL-OCC-YR	300	0.00	450	250	200
51	EL2 (FL2) Electrical Closet 2	EL2 Second floor	Electrical/Mechanic	NULL-OCC-YR	300	0.00	450	250	200
52	EL3 (FL3) Electrical Closet 3	EL3 Third floor	Electrical/Mechanic	NULL-OCC-YR	300	0.00	450	250	200

INSIGHT USES


From Concept to Documentation

Discover how Revit and
Insight are used in
designing a net-zero
project from concept to
documentation

Diverse Simulation Types Approaches to Net Zero
Diverse Level of Details Adoptions to Design Stages



SIMULATION TYPES



BASELINE

National Median Site Energy Use Intensity (kBtu/s)
Laboratory/Mix Use 78.8
College/University 130.7

Optimized Massing & Orientation

- Daylight Optimization
- Solar Heat Gain Optimization
- Internal Heat Loss Optimization
- Floor Plan Layout Optimization

Enhanced Envelope & Material

- Natural Daylight Harvesting
- Optimized Solar Shading
- High Performance Glazing
- Well Insulated Opaque Walls
- Green Roof

Advanced HVACe Systems

- 15.0 Heat Recovery System
- Variable Refrigerant Flow (VRF) System
- Dedicated Outdoor Air (DOAS) System
- LED Lighting/Dimming
- Ground Source Heat Pump

Augmented Smart Building System

Renewable Energy

BUILDING EUI 79






68

58


32



24

0




LEVEL OF DETAILS





Massing LOD 100





- Massing Orientation
- Energy Projection

Massing LOD 200



- Design Optimization
- Daylight and Heat Gain/ Loss Trade-off








Facade LOD 200

- Window-to-wall Ratio
- Thermal Properties - glazing types, wall constructions

Facade LOD 300

- Geometry Optimization - solar shades, insulation thickness
- Daylight and Heat Gain/ Loss Trade-off

Facade Design Optimization



Daylight Analysis Metric


Annual Sunlight Exposure (ASE_{1000,250})

describes the potential for visual discomfort in interior work environments.

% of the floor area that is exposed to >1000 lux of direct sunlight for >250 hours per year


Current Scenario

9" Spacing
25 deg tilted



Proposed Scenario

8" Spacing
35 deg tilted



[LEED Daylight credit requires ASE_{1000,250}<10%]

Symposium
ASE_{1000,250}=17%



Multi-use Lab
ASE_{1000,250}=16%





ASE_{1000,250} fail
ASE_{1000,250} pass



Symposium
ASE_{1000,250}=8%



Multi-use Lab
ASE_{1000,250}=5%

% of the floor area in Direct Sun every hour





PV LOD 200

- Solar Radiation Analysis
- PV Capacity Assessment

PV LOD 300

- PV System Optimization - Orientation, Tilt, Layout
- PV System Configuration - capacity and efficiency
- Payback Years Assessment

Study Settings

Weather Data: ID 51396 - 40.8388710021973,-72.9930801391602

Analysis Period: Full Annual

Building Area: <user entered> 2,400 m²

Building Energy: EUI 110 kWh/m²/year

Electricity Cost: \$0.18 / kWh 0.0 % escalation

Panel Type: 18.6% \$3.06/Installed Watt

Coverage: 75% of selected surface area

Payback Filter: 30 year payback limit

Analysis Grid: 9.62 foot grid, 190 analysis points

Coarse Fine

Apply

Solar Analysis

Study Type: Solar Energy - Annual PV

Surfaces: <user selection>

Results

PV Energy Production
349,843 kWh/year
\$62,972 energy savings

Building Energy Offset
133% of 264,000 kWh/year
11.0 years payback

v1.0.0.19



- Weather Data
- Analysis Period
- Three Pre-set PV Settings
- Surface Selection
- Fixed Context Shading



- Weather Data
- Analysis Period
- Customized Real PV Modules
- Surface Selection
- Dynamic Context Shading
- System Loss Factor

METHODOLOGY

How we ensure the best results?

Discover the best
approaches to modeling
in Revit for reliable
environmental simulation
results

Responsibilities Clarify BEM Roles in BIM
Standards Well Defined Building Elements
Best Practices Well Structured BIM Model



METHODOLOGY


RESPONSIBILITIES

Clarify BEM Roles in BIM



Project Timeline and Core Team Structure																
PRE-DESIGN		SKETCH STUDY		PRELIMINARY DESIGN			CONTRACT DOCUMENT			PERMITTING/ BIDDING		CONSTRUCTION ADMINISTRATION		TRAINING		
1st MAR 2017	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	JAN 2018	MAY	JUN 2018	JUN	JUL	AUG 2019
Workflow Simulation Software																
HP Design Objectives	HP Design Objectives															
Certifications	Certifications	Certifications	Certifications	Certifications	Certifications	Certifications	Certifications	Certifications	Certifications	Certifications	Certifications	Certifications	Certifications	Certifications	Post-Occupancy Evaluation Data Sharing	
Climate Analysis	Climate Condition React	Climate Condition React														
Passive Strategies Research (List)	Passive Strategies Implement (Drawings)	Passive Strategies Implement (Drawings)	Passive Strategies Implementations (Drawings) (Concept to Reality)													
	Conceptual Comfort Analysis	Adaptive Comfort Analysis (ASHRAE Standard 55)	Adaptive Comfort Analysis (ASHRAE Standard 55)													
	Building Archetype (3 options/Solutions) (Massing Orientation) (Window Ratio) (Solar Exposure) (Daylighting) (CFD/MicroFlo) (Multi-Variable Optimize)	Integrated Architectural Design Development	Integrated Construction Document													
		Envelope Design (Fenestrations) (Envelope Material) (Shading Devices) (Thermal/Hygrothermal Analysis) (Daylighting Validation) (CFD/MicroFlo Analysis)														
	Program Validation	Profile Setup (Occupancy) (Schedule) (Internal Load)														
		Baseline Model (building type and area) Identify the Largest Contributors to Energy														
		Renewable Energy Potential Energy Reduction Goal	Renewable Energy Systems Design	Renewable Energy Systems Finalize												
			HVAC Options Design (Mechanical Design) (Lighting & Daylighting) (Water Fixtures)	Finalize HVAC Systems (Mechanical Sizing) (Lighting Optimization) (Water Fixtures) (All other details) (Specifications)												
	Cost Modeling	Cost Modeling	Payback/ Lifecycle Cost Check	Cost Verification											Proper Substitutions	

BIM/ BEM roles need to be clearly defined in each design stage. For example, architects own the settings of the geometry, but energy modelers can take the control of the materials if the person has the specialties on this.



Client

Design Criteria Approval;
Energy Goals Approval;



Architect/ Engineer

Design Criteria Setups;
Review Model Issues;




High Performance Designer

BEM Simulation;
Energy Goals Verification;
BEM/ BIM Standard



BIM Manager/ BIM Coordinator

BEM/ BIM Templates;
BIM Coordination;



Client

Design Criteria Approval;
Energy Goals Approval;



Architect/ Engineer

Design Criteria Setups;
Review Model Issues;



High Performance Designer


Energy Goals Verification;
BEM Simulation;



BIM Manager/ BIM Coordinator

BEM/ BIM Templates;
BIM Coordination;


LOD100 PRE-DESIGN



Building Code Check;
Design Criteria Setups;
Program Matrix;
Room Date Sheet Develop;

Climate Analysis;
EUI Projection;
Energy code/ Performance
Goals verification;

Project BIM Global Setup;
Import Previous BIM/ BEM
Templates;



Client

Design Criteria Approval;
Energy Goals Approval;



Architect/ Engineer

Design Criteria Setups;
Review Model Issues;



High Performance Designer


Energy Goals Verification;
BEM Simulation;



BIM Manager/ BIM Coordinator

BEM/ BIM Templates;
BIM Coordination;

LOD200 PRELIMINARY DESIGN




Programming Stacking;
Setup the building geometry
and Rooms in Revit with
internal loads and occupancy
schedule assumptions defined;

Massing Orientation Analysis;
Facade Glazing % Test;

Conceptualization on Facade
assembly, fenestration and
shadings, and HVAC options

Setup default BEM parameters
for primary family types (walls,
glazing, floors, roof, rooms,
spaces)



Client

Design Criteria Approval;
Energy Goals Approval;



Architect/ Engineer

Design Criteria Setups;
Review Model Issues;



High Performance Designer


Energy Goals Verification;
BEM Simulation;



BIM Manager/ BIM Coordinator

BEM/ BIM Templates;
BIM Coordination;

LOD300 DETAILED DESIGN




Preferred Facade Suppliers;
HVAC Sizing and Sequence of
Operation;

Daylight Analysis;
Finalize facade thermal/
daylight performance;

Setup the Spaces in Revit with
data transferred from Rooms;
Energy modeling within Insight
and/ or exported to IES VE for
HVAC design optimization;

Setup BEM schedules for
daylight/ energy reports and
design documentation;



Client

Design Criteria Approval;
Energy Goals Approval;



Architect/ Engineer

Design Criteria Setups;
Review Model Issues;



High Performance Designer


Energy Goals Verification;
BEM Simulation;



BIM Manager/ BIM Coordinator

BEM/ BIM Templates;
BIM Coordination;

LOD400
INSTRUCTION DOCUMENTATION



Code Compliance Checking;
Product Specifications;

Code Compliance Modeling;
Finalize Daylight Reports;
Finalize Energy Reports;


Final Deliverables
Coordination;
BIM/ BEM Templates Updates;

METHODOLOGY
STANDARDS



Well-Defined Building Elements






BEM Conceptual



BEM Detailed



LOD100 PRE-DESIGN	LOD200 PRELIMINARY DESIGN	LOD300 DETAILED DESIGN	LOD400 CONSTRUCTION DOCUMENTATION
			
<ul style="list-style-type: none">• <u>Early Projection</u>• Location and context;• Facade types;• Building Type: Building level thermal profile and occupancy;	<ul style="list-style-type: none">• <u>Preliminary Analysis</u>• Spatial geometry;• Facade properties;• Space Type: Space level thermal profile and occupancy;• Method of servicing. heating/ cooling/ ventilation;	<ul style="list-style-type: none">• <u>Simulation/ Optimization</u>• Fixed spatial geometry;• Detailed facade construction;• Fixed building profile;• Servicing schedules. sequence of operations;	<ul style="list-style-type: none">• <u>Integration/ Documentation</u>• Fixed spatial geometry;• Facade thermal bridging/ infiltration;• Fixed building profile;• Fixed sequence of operations;




Envelope LOD 200

- Construction defined in Energy Settings
- Energy Settings - Advanced - Other Options - Material Thermal Properties - Schematic Types

Envelope LOD 300

- Construction modeled with material thermal properties
- Properties - Construction - Structure - Edit Assembly - Material - Thermal

Envelope Thermal



Type Properties

Family: System Family: Basic Wall
Type: SCCC_Generic - 12" - External

Type Parameters

Parameter	Value
Construction	Structure
Wrapping at Inserts	Interior
Wrapping at Ends	Interior
Width	1' 0"
Function	Exterior
Graphics	Coarse Scale Fill Pattern: Black
Materials and Finishes	Structural Material: Material
Analytical Properties	Heat Transfer Coefficient (U): 0.0312 BTU/(h·ft ² ·°F) Thermal Resistance (R): 32.0169 (h·ft ² ·°F)/BTU Thermal mass: 2.5002 BTU/°F Absorptance: 0.700000 Roughness: 3
Identity Data	Type Image: Keynote Model: Manufacturer Type Comments: URL Description: West Assembly Description: Assembly Code: B2010 Type Mark:

Edit Assembly

Family: Basic Wall
Type: SCCC_Generic - 12" - External
Total thickness: 1' 0"
Resistance (R): 32.0169 (h·ft²·°F)/BTU
Thermal Mass: 2.5002 BTU/°F
Sample Height: 20' 0"

Layers

Function	Material	Thickness	Wraps	Structural Material
1 Finish 1 [4]	Concrete, Cast-in-Place gr	0' 0 1/4"	<input checked="" type="checkbox"/>	<input type="checkbox"/>
2 Thermal/Air Layer [3]	SCCC_Exterior Thermal	0' 3 1/2"	<input checked="" type="checkbox"/>	<input type="checkbox"/>
3 Core Boundary	Layers Above Wrap	0' 0"	<input type="checkbox"/>	<input type="checkbox"/>
4 Structure [1]	SCCC_Exterior Thermal_S	0' 8"	<input type="checkbox"/>	<input type="checkbox"/>
5 Core Boundary	Layers Below Wrap	0' 0"	<input type="checkbox"/>	<input type="checkbox"/>
6 Finish 2 [5]	SCCC_Interior Wall Finish	0' 0 1/4"	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Material Browser - SCCC_Exterior Thermal

Search: Project Materials: ...

Name
_SCCC_Backface_Metal
_SCCC_Boral Siding
_SCCC_Exterior Paver
_SCCC_Exterior Thermal
_SCCC_Exterior Thermal_Stud
_SCCC_Interior Ceiling Finish
_SCCC_Interior Floor Finish
_SCCC_Interior Glazing
_SCCC_Interior Thermal

Properties

- Transmits Light:
- Behavior: Isotropic
- Thermal Conductivity: 0.0300 btu/(hr·ft·°F)
- Specific Heat: 0.2006 btu/(lb·°F)
- Density: 8.74 pound per cubic foot
- Emissivity: 0.90
- Permeability: 0.0000 grain/(ft²·hr·inHg)
- Porosity: 0.01
- Reflectivity: 0.00
- Electrical Resistivity: 1.0000E+10 Ω·m


Construction Settings.

Edit Assembly: Assembly Layers.

Material Settings.

Material Browser Thermal Tab. Swap out different assets for each material or edit the properties.

Envelope Thermal





Energy Settings. Check Detailed Elements.



Revit will use the thermal properties assigned to each element and those results will be represented in the “BIM Settings” triangle in each Insight factor.

Envelope Daylight

SCCC - LEED - sDA/ASE Results Summary
First Floor



AECOM High Performance Buildings
04/26/2019



Analytical properties are for energy analysis, not illuminance analysis

Tvis properties are defined by changing the custom color




Envelope Daylight

Tvis properties are defined by changing the custom color

- determine # of panes in the model
- determine the thickness of window pane
- determine the Tvis value
- set color of glass material to RGB values

		Tvis								
	Thickness	90%	80%	70%	60%	50%	40%	30%	20%	10%
single	3.0 mm	171	24	2	0	0	0	0	0	0
	4.0 mm	189	43	8	1	0	0	0	0	0
	5.0 mm	201	61	16	3	0	0	0	0	0
	6.0 mm	209	78	25	7	1	0	0	0	0
	8.0 mm	219	105	45	17	5	1	0	0	0
	10.0 mm	226	125	64	29	11	3	0	0	0
	12.7 mm	232	146	86	47	22	9	3	0	0
	25.4 mm	243	193	148	109	76	49	27	12	3
	28.6 mm	244	199	157	120	87	59	35	17	5
dual	3.0 mm	-	154	50	14	3	0	0	0	0
	4.0 mm	-	175	76	29	9	2	0	0	0
	5.0 mm	-	189	96	44	18	5	1	0	0
	6.0 mm	-	198	113	59	28	11	3	0	0
	8.0 mm	-	211	139	86	48	24	9	2	0
	10.0 mm	-	-	137	58	21	6	1	0	0
triple	3.0 mm	-	-	160	84	39	15	4	0	0
	4.0 mm	-	-	175	105	57	27	10	2	0
	5.0 mm	-	-	186	121	73	39	17	5	0
	6.0 mm	-	-	224	118	55	21	6	1	0
	8.0 mm	-	-	232	143	81	40	16	4	0
quad	3.0 mm	-	-	236	160	101	58	28	10	1
	4.0 mm	-	-	239	173	118	74	40	17	4
	5.0 mm	-	-	-	-	-	-	-	-	-
	6.0 mm	-	-	-	-	-	-	-	-	-

Space Thermal



Definition

- Space Name
- Space Number
- Space definitions should be matching to room definitions and can be automatically transferred from rooms

Geometry

- Space Area
- Space Height
- The walls, doors, and windows generating rooms, spaces, and zones should be defined as Room Bounding

Utilization

- Occupancy and Schedule
- Lighting and Equipment Power Density
- assigned usages and behavioral attributes should be defined via different Space Types

<Building>	
Active Storage	
Active Storage - Hospital/Healthcare	
Air/Train/Bus - Baggage Area	
Airport - Concourse	
Atrium - Each Additional Floor	
Atrium - First Three Floors	
Audience/Seating Area - Auditorium	
Audience/Seating Area - Convention Center	
Audience/Seating Area - Court House	
Audience/Seating Area - Exercise Center	
Audience/Seating Area - Gymnasium	
Audience/Seating Area - Motion Picture Theatre	
Audience/Seating Area - Penitentiary	
Audience/Seating Area - Performing Arts Theatre	
Audience/Seating Area - Police/Fire Stations	
Audience/Seating Area - Religious	
Audience/Seating Area - Sports Arena	
Bank Customer Area	
Banking Activity Area	Office

Properties

FIRST FLOOR LIGHTING PLAN O...

R

Spaces (1) Edit Type

Electrical - Loads

Design HVAC Load ... 0.00 W/ft²


Design Other Load p... 0.00 W/ft²

Actual Lighting Load 163.20 VA

Actual Other Load 0.00 VA


Actual Power Load 720.00 VA


Actual Receptacle L... 2160.00 VA



SPACE SCHEDULE							
A	B	C	D	E	F	G	H
Name	Space Type	Area	Area per Per	Specified Lighting Load	Specified Power Load	Outdoor Air p	Outdoor Air per Area
Admin	BBJ Admin	2968 SF	200 SF	0.30 W/ft ²	0.75 W/ft ²	5.0 CFM	0.06 CFM/SF
Barber	BBJ Multi-purpose	602 SF	10 SF	0.40 W/ft ²	0.50 W/ft ²	7.5 CFM	0.06 CFM/SF
Cell	BBJ Cell	65693 SF	40 SF	0.64 W/ft ²	0.10 W/ft ²	5.0 CFM	0.06 CFM/SF
Central Control	BBJ Central Control	5910 SF	200 SF	0.30 W/ft ²	0.75 W/ft ²	5.0 CFM	0.06 CFM/SF
Children's Play	BBJ Community	1423 SF	10 SF	0.62 W/ft ²	1.00 W/ft ²	7.5 CFM	0.12 CFM/SF
Clinic	BBJ Medical	15475 SF	50 SF	0.56 W/ft ²	5.00 W/ft ²	15.0 CFM	0.00 CFM/SF
Community	BBJ Community	36374 SF	10 SF	0.62 W/ft ²	1.00 W/ft ²	7.5 CFM	0.12 CFM/SF
Concourse	BBJ Corridor	108192 SF	1000 SF	0.41 W/ft ²	0.10 W/ft ²	0.0 CFM	0.06 CFM/SF
Conference	BBJ Admin	1636 SF	200 SF	0.30 W/ft ²	0.75 W/ft ²	5.0 CFM	0.06 CFM/SF
Cooking	BBJ Multi-purpose	1430 SF	10 SF	0.40 W/ft ²	0.50 W/ft ²	7.5 CFM	0.06 CFM/SF

LIGHTING SCHEDULE							
A	B	C	D	E	F	G	H
Space: Name	Count	Type	Manufacturer	Description	Model	Wattage	Apparent Load
FIRST FLOOR							
ADMIN CLERK	1	B	LITHONIA	VOLUMETRIC 2x4 LED	2BLT4-40L-ADSM-MVOLT-GZ10-LP835	61 W	32 VA
CAI CLASSROOM	1	C1	LITHONIA	4" ROUND OPEN LED DOWNLIGHT	LDN4-35/15-L04-AR-LD-MVOLT-GZ10	8 W	20 VA
CL	2	C1	LITHONIA	4" ROUND OPEN LED DOWNLIGHT	LDN4-35/15-L04-AR-LD-MVOLT-GZ10	8 W	41 VA
CONFERENCE RO	15	C1	LITHONIA	4" ROUND OPEN LED DOWNLIGHT	LDN4-35/15-L04-AR-LD-MVOLT-GZ10	8 W	306 VA
CORRIDOR	4	C1	LITHONIA	4" ROUND OPEN LED DOWNLIGHT	LDN4-35/15-L04-AR-LD-MVOLT-GZ10	8 W	82 VA
ELEVATOR	2	K	LITHONIA	2" GASKETED LED	DMW2-L24-4000LM-ACL-WD-MVOLTZ10-35K-80	0 W	80 VA
ENTRY VESTIBUL	4	C1	LITHONIA	4" ROUND OPEN LED DOWNLIGHT	LDN4-35/15-L04-AR-LD-MVOLT-GZ10	8 W	82 VA
JANITOR	1	C1	LITHONIA	4" ROUND OPEN LED DOWNLIGHT	LDN4-35/15-L04-AR-LD-MVOLT-GZ10	8 W	20 VA

Lighting LOD 200 

Lighting LOD 300 

- LPD defined in each space
- Space Type Settings - Lighting Load Density
- Check in Space Schedule

- LPD calculated with actual lighting fixtures
- Electrical - Loads - Actual Lighting Load
- Check in Lighting Fixture Schedule

METHODOLOGY

BEST PRACTICES


Well-Structured Building Model



Best Practice


First Checklist

- Be sure to set Location
- Check True North/ Project North
- Check Energy Settings:
 - Be sure to set building type
 - Always use the combined mode
 - Try to set the analytical space/ surface resolution to 8"/ 4"
- Specify ground plane
- Check if the facade thermal properties are defined
 - Construction Settings
 - Material Settings
- Check if the spaces are placed throughout the model
- Check if the space types are defined



- **Focus the model**





- Create your own Revit energy model view
- Delete elements not required for energy analysis, such as railings and furnishings
- Create your own schedules for BEM relevant elements



Best Practice

Walls

- Place walls based on their centerlines;
- Substitute simple one layer for walls. Avoid multi-layers;
- Set walls that protrude into a space to “non-room bounding”;
- For gbXML exporting: revit constructions are not utilized by IES VE. therefore at the “Set Model Properties” dialog, identify these at the building and/ or room level
- For gbXML exporting: the same wall type used for the exterior can be used for the interior. The gbXML export process will differentiate between internal and external walls automatically



Best Practice

Floors

- **Finished Floors:** Avoid separately modeled finished floor or model the finished floors as non-room boundary.

- **Outside Floors:** Disable room bounding of outside floor elements such as plaza and walkways.

- **Atriums:** Avoid openings on the floors. Better to identify room on each floor separately.

- **Attach Walls:** After completing the floor, you will be prompted “Would you like walls that go up to this floor’s level to attach to its bottom?” Answer NO to this prompt.

Revit Envelope

<Exterior Wall Schedule>					
A	B	C	D	E	F
Mark	Family	Type	Area	Heat Transfer Coefficient (U)	Thermal Resistance (R)
	Basic Wall	SCCC_Generic - 12" - External	6,338.92 SF	0.0312 BTU/(h·ft²·°F)	32.0169 (h·ft²·°F)/BTU
	Basic Wall	SCCC_INSULATION - 2"	1,407.83 SF	0.2024 BTU/(h·ft²·°F)	4.9397 (h·ft²·°F)/BTU
	Basic Wall	SCCC_INSULATION - 5 1/4"	352.35 SF	0.0717 BTU/(h·ft²·°F)	13.9539 (h·ft²·°F)/BTU
	Basic Wall	SCCC_INSULATION - 8"	1,081.42 SF	0.0465 BTU/(h·ft²·°F)	21.4955 (h·ft²·°F)/BTU
	Basic Wall	SCCC_Roof 6"	1,543.81 SF	0.0601 BTU/(h·ft²·°F)	16.6417 (h·ft²·°F)/BTU

IES VE Envelope

STD_WAL2	External Wall	Y	H1A 400mm Insul concrete Wall	Generic	0.3362	525.000	
STD_WAL3	External Wall	Y	H1A 500mm Uninsulated concrete Wall	Generic	1.9730	500.000	
STD_WAL7	External Wall	Y	H1A 600mm Insul concrete Wall	Generic	0.3206	725.000	
construction layers (Outside To Inside)							
	Material	Thickness mm	Conductivity W/(m·K)	Density kg/m³	Specific Heat Capacity J/(kg·K)	Resistance m²K/W	Vapour Resistivity G (m²·kg/m³)
STD_WL5	Plasterboard	5.0	0.2300	750.0	1000.0	0.0220	0.000
STD_WP12	H1A R3.44/inch Rockwool insulation	100.0	0.0418	30.0	1830.0	2.7509	- (insulating material)
W003	CAST CONCRETE (REHUSIM)	250.0	1.4000	2160.0	840.0	0.1795	500.000
LSGP001	GYPSUM/PLASTER BOARD - HF-E1 (ASHRAE)	20.0	0.1610	801.0	237.0	0.1243	45.000

General	JA4	Layers
Material	R/W	
Stucco - 3/8 in	0.2	
Vapor permeable net - 1/8 in	0.1	
Expanded Polystyrene EPS - 1 in, R4.2	4.2	
Plaster - 5/8 in	0.8	
Metal Frame Wall - 16x10C - 2x6 - R19 ins.	3.9	
Gypsum Board - 5/8 in	0.6	
Properties		
U-Factor	0.056	R-value

eQuest Envelope

	Exterior Wall Name	Parent Space	Multiplier	X (ft)	Y (ft)	Z (ft)	Height (ft)	Width (ft)	Azimuth (deg)	Tilt (deg)	Location	Construction
64	EL2 North Wall (G.NE5.E6)	EL2 (FL2) Classroom	1	0.00	0.00	0.00	9.50	29.75	-180.00	90.00	V1 of Space Poly	PS710 60DD Exterior
65	EL2 North Wall (G.NW28.E25)	EL2 Plenum NW Cla	1	0.00	29.25	0.00	3.50	29.25	-90.00	90.00	V8 of Space Poly	PS710 60DD Exterior
66	EL2 North Wall (G.NW7.E9)	EL2 (FL2) Classroom	1	0.00	29.25	0.00	9.50	29.25	-90.00	90.00	V8 of Space Poly	PS710 60DD Exterior
67	EL2 South Wall (G.SE1.E2)	EL2 (FL2) Classroom	1	0.00	29.50	0.00	9.50	29.50	-90.00	90.00	V8 of Space Poly	PS710 60DD Exterior
68	EL2 South Wall (G.SE22.E18)	EL2 Plenum SE Cla	1	0.00	29.50	0.00	3.50	29.50	-90.00	90.00	V8 of Space Poly	PS710 60DD Exterior
69	EL2 South Wall (G.SW18.E14)	EL2 (FL2) Classroom	1	0.00	0.00	0.00	9.50	29.50	-180.00	90.00	V1 of Space Poly	PS710 60DD Exterior
70	EL2 South Wall (G.SW39.E30)	EL2 Plenum SW Cla	1	0.00	0.00	0.00	3.50	29.50	-180.00	90.00	V1 of Space Poly	PS710 60DD Exterior
71	EL2 West Wall (G.C16.E13)	EL2 (FL2) Corridor	1	0.00	0.00	0.00	9.50	9.10	-180.00	90.00	V1 of Space Poly	PS710 60DD Exterior
72	EL2 West Wall (G.C37.E29)	EL2 Plenum Corrido	1	0.00	0.00	0.00	3.50	9.10	-180.00	90.00	V1 of Space Poly	PS710 60DD Exterior
73	EL2 West Wall (G.NW28.E24)	EL2 Plenum NW Cla	1	0.00	0.00	0.00	3.50	33.85	-180.00	90.00	V1 of Space Poly	PS710 60DD Exterior
74	EL2 West Wall (G.NW7.E8)	EL2 (FL2) Classroom	1	0.00	0.00	0.00	9.50	33.85	-180.00	90.00	V1 of Space Poly	PS710 60DD Exterior

Best Practice


Spaces

- Set Volume Computations to “Areas and Volumes”.
- Make sure spaces are placed throughout the entire model
 - In Visibility Graphics, turn on Spaces - In fill and reference
 - Visually check the model in plan view and in section view
 - Pay attention to shafts and chase walls
 - Create space schedule and remove undefined spaces
- Separate out room-bounding and non room-bounding
 - Focus the BEM model and turn off non-related elements
 - Check or uncheck room bounding elements when necessary
 - Verify all walls and floors are room bounding

Revit Space

<Space Schedule>								
A	B	C	D	E	F	G	H	I
Name	Space Type	Area	Area per P	Specified Light	Specified Powe	Outdoor Air p	Outdoor Air pe	Specified Exha
Admin	BBJ Admin	2968 SF	200 SF	0.30 W/ft ²	0.75 W/ft ²	5.0 CFM	0.06 CFM/SF	0.00 CFM
Barber	BBJ Multi-purpos	602 SF	10 SF	0.40 W/ft ²	0.50 W/ft ²	7.5 CFM	0.06 CFM/SF	0.00 CFM
Cell	BBJ Cell	65693 SF	40 SF	0.64 W/ft ²	0.10 W/ft ²	5.0 CFM	0.06 CFM/SF	1.00 CFM
Central Control	BBJ Central Contr	5910 SF	200 SF	0.30 W/ft ²	0.75 W/ft ²	5.0 CFM	0.06 CFM/SF	0.00 CFM
Children's Play	BBJ Community	1423 SF	10 SF	0.62 W/ft ²	1.00 W/ft ²	7.5 CFM	0.12 CFM/SF	0.00 CFM
Clinic	BBJ Medical	15475 SF	50 SF	0.56 W/ft ²	5.00 W/ft ²	15.0 CFM	0.00 CFM/SF	
Community	BBJ Community	36374 SF	10 SF	0.62 W/ft ²	1.00 W/ft ²	7.5 CFM	0.12 CFM/SF	0.00 CFM
Concourse	BBJ Corridor	108192 SF	1000 SF	0.41 W/ft ²	0.10 W/ft ²	0.0 CFM	0.06 CFM/SF	0.00 CFM
Conference	BBJ Admin	1636 SF	200 SF	0.30 W/ft ²	0.75 W/ft ²	5.0 CFM	0.06 CFM/SF	0.00 CFM

IES VE Space




eQuest Space

	Space Name	Parent Floor	Activity Desc.	Occupancy Schedule	Area/Person (ft ²)	Number of People	Total Ht Gain (Btu/h-person)	People Sens (Btu/h-person)	People Lat (Btu/h-person)
45	EL3 (FL3) Nurse's Office	EL3 Third floor	Healthcare - Exam	OFFICE-OCC-YR	58	1.00	450	250	200
46	EL1 (FL1) Warming Pantry	EL1 First floor	Food Preparation	KITCHEN-OCC-YR	200	11.00	450	275	275
47	EL2 (FL2) Exercise Room	EL2 Second floor	Exercise Room	GYM-OCC-YR	17	31.00	450	710	1,090
48	EL1 (FL1) Domestic Water S	EL1 First floor	Electrical/Mechanic	NULL-OCC-YR	300	0.00	450	250	200
49	EL1 (FL1) Refuse/Recycle	EL1 First floor	Electrical/Mechanic	NULL-OCC-YR	300	0.00	450	250	200
50	EL2 (FL2) Telecom	EL2 Second floor	Electrical/Mechanic	NULL-OCC-YR	300	0.00	450	250	200
51	EL2 (FL2) Electrical Closet 2	EL2 Second floor	Electrical/Mechanic	NULL-OCC-YR	300	0.00	450	250	200
52	EL3 (FL3) Electrical Closet 3	EL3 Third floor	Electrical/Mechanic	NULL-OCC-YR	300	0.00	450	250	200

Best Practice

Spaces

- Define all upper and lower boundaries of the spaces
 - Ceilings. Determine whether or not the plenum area is conditioned. If so, plenum area must be included in a space; If not, plenum area must be defined as a separate space.
 - Space offset on the level. Use a section to inspect the vertical shape of the space to ensure it is properly aligned. Ensure the space goes from top of slab to top of slab (level to level) with limit offset defined as zero. (no offset from the level)
 - Space offset above the roof. For spaces on the top floor, use a limit offset of 1' so that the space rises above the roof element.




Best Practice

Troubleshooting


- **Unexpected shades elements inside the model.**

- Make sure that there are no air gaps within the full external boundary
- Lower analytical space and surface resolution if there are significant gaps in the model surface



- **Model results are completely gray shaded spaces.**

- Be sure to specify the origin point somewhere in the center of the model
- Transfer project standards from Revit default template to avoid overly complicated revit templates




PICK N CHOOSE



Comparisons: Insight vs IES VE vs Honeybee




Learn the pros /cons
when comparing Insight,
IES VE, and Honeybee,
and select the tool that is
right for your project

BIM solutions offer some of the energy modeling functionality today, but more is needed.







	Insight	IES VE	Honeybee
Design Tool/ Engineering Tool	D	E	D/E
Architect/ Engineer	A/E	E	A

	 Insight	 IES VE	 Honeybee
APPLICATIONS	<p>energy modeling. daylight analysis. solar study. heating/ cooling loads calculation. Cloud-based simulation. Revit Integration. customized zoning.</p>	<p>energy modeling. daylight analysis. solar study. heating/ cooling loads calculation. Revit Convertible. customized zoning. customized HVAC configuration.</p>	<p>energy modeling. daylight analysis. solar study. heating/ cooling loads. customized zoning. customized HVAC [w/ Ironburg]. customized visualization. parametric optimization.</p>
SOFTWARE USES	<p>Quick energy/ daylight analysis and high-level estimates. Guide design decision at early stages (SD). Understand the performance and provide feedback seamlessly throughout the design process.</p>	<p>Code compliance energy modeling and Net Zero Energy achievability verification (CD). Detailed thermal dynamic simulation with customized zoning and HVAC.</p>	<p>Multi-variable and Multi-objective energy/ daylight/ cost trade-off optimizations (DD). Customized visualization for presentation and communication.</p>



IES

Insight



PERFORMANCE

Develop Sustainability Workflow in BIM



Two New Questions

Question 4

No single software can cover all types of projects in all phases of design?

NO


- A hybrid utilization of different BEM programs is needed with BIM integration.
- Multi-level capabilities are required for a high performance designer;
- Holistic thinking is also needed when driving a sustainability project.

Question 5

BIM or BEM data is not readily available from most manufacturers?

NO

- Energy-relevant specifications from equipment manufacturers are needed.
- BIM guidelines and templates should be developed for BEM with good assumptions made ready from a good database.



“Form follows performance, with the balancing of the budget.”



AUTODESK®

Make anything™

Autodesk and the Autodesk logo are registered trademarks or trademarks of Autodesk, Inc., and/or its subsidiaries and/or affiliates in the USA and/or other countries. All other brand names, product names, or trademarks belong to their respective holders. Autodesk reserves the right to alter product offerings and specifications at any time without notice, and is not responsible for typographical or graphical errors that may appear in this document.

© 2019 Autodesk. All rights reserved.

